

AURES[®]



sango



sango

irresistible epos

sango

sango - from the **AURES** Group - is an exclusive design concept of integrated EPOS: one of its many unique features is to completely free-up the space under the touch screen.

With no intrusive stand, it soars effortlessly, as if weightless, offering and revealing a space traditionally occupied by the central unit. Elegantly suspended on its offset cast aluminium arm, the real exo-skeleton of the EPOS terminal and support for its technological core (CPU), **sango** combines minimalist lines, ergonomics and low power consumption (fanless system).

It is proposed with an SSD Flash Disk (solid state drive 2.5"), for increased reliability. Stable and rigid, its thin metal base - a natural extension of the slender and beautifully - designed arm - acts as a heat sink.

sango will adapt to the technology requirements of all users: 4 types of processors are available, to suit their needs, as well as a range of connection options. The flat LED touch monitor, with an edgeless display surface, is offered in multi-touch projected capacitive technology (PCAP).

Enhanced by the finish of the polycarbonate, **sango**'s *seven interchangeable colours* (*White, Black, Red, Blue, Orange, Grey & Cassis*) fit into the revolution line started by **AURES** in 2005 and provide the final touch for the brand image and visual identity of all points of sale and points of service.

		Other specifications
Processors INTEL Ivy Bridge i5 - 3337U INTEL Ivy Bridge i3 - 3217U INTEL Ivy Bridge 1047 UE INTEL Cedar View D2550	INTEL HD Graphics 4000 core	External power supply 65W (19V/4.7A adaptor)
Chipset INTEL HM76 or NM10	Connections Front: 2 x USB3.0 / or 2 x USB2.0 Rear: 2 x USB2.0 + 2 x USB3.0 / or 4 x USB2.0	Net weight: 8.70kg (not including power supply or customer display)
Memoiry SO-DIMM DDR3 x1 - up to 4 GB (1067 MHz) SO-DIMM DDR3 x 1 - up to 8 GB (1333/1666 MHz)	Serial / COM ports 4 x RJ45 (including 2 powered) 1 x LAN (10/100/1000) 1 x cash-drawer port 1 x display port (2 nd screen)	Dimensions (working position - tilted at 45°) W x H x D: 410 x 400 x 260 mm
		Compatible OS Windows 8 Industry, Windows 7 Pro, POSready 7, POSready 2009, Linux

Associated peripherals (options): ODP 333 receipt printer, 3S 333 cash drawer, 1D & 2D barcodes, Cards, Dallas & Addimat keys readers, graphic customer displays, integrated or external, 2nd screen: at the back of the system (integrated), or standalone (external)



AURES®



www.aures.com

