

Ultra-compact, fully adjustable EPOS system



Small and reliable, **ninô** by AURES is a compact and fully adjustable EPOS.

With its sleek modern appearance and capabilities, **ninô** is an ultra-compact, fully adjustable EPOS, with the specificity of being able to fold flat; it is perfectly suited for most retail and point of sale sectors.

It has a 14 inch 16:9 format style touchscreen (PCAP or resistive touch panel) and is designed to be no bigger than a small desktop, with full EPOS functionalities. Thanks to its completely flexible and adjustable swing arm, which is attached to the die-cast aluminium base, it can be folded flat or adjusted to all viewing angles from flat to 90°. This means it can

be used "flat" like a console, on its base, or mounted on a wall or pole (several mounting accessories, as well as VESA fixings, are available).

Fanless, equipped with an HDD (SSD is optional) - it is perfect for harsh environments and always in tune with the new environmental standards (low energy consumption and small carbon footprint).

It is the ideal companion for all pop-up stores and shops, for take away food & non-food specialists, including food & catering trucks, mobile canteens, etc.



- Intel Cedar View D2550 processor
- Edgeless flat touchscreen (PCAP / resistive panel in option)
- Small, ultra compact EPOS – able to fold flat
- HDD 2.5" (or SSD in option)
- Base fully adjustable from flat to 90°
- 4 serial ports, 4 USB ports
- Display Port with HDMI support
- +12 V output for peripheral power supply
- Low power consumption & small foot print
- Manifold system: base, pole or wall mounting options



MODEL

ninô

Processor	Intel Atom Cedar View D2550
Chipset	NM10
Memory	DDR3 SODIMM 2GB in standard - up to 4GB (2 sockets)
HDD	2.5" - (or optional SSD)
LCD	14" TFT (1366 x 768) – LED back light
Touchscreen	PCAP edgeless (or true flat resistive in option)
Brightness	220 cd/m ² with auto dim

I / O P O R T S

Serial	4 x serial ports with + 12V power option
USB	4 x USB 2.0 ports
Power out	+ 12 volts for peripheral power
LAN	10/100/1000 Base-T
2 nd Display	Display Port with support for HDMI, DVI et VGA (with adaptor)
Cash drawer	1 x 12 V or 24 V
Audio/sound	internal speakers and combo headset + mic jac
Power input	19VDC from 65W power adaptor mounted in base
Mini-PCI Express	1 internal mini PCI Express slot (for WIFI)

E N V I R O N M E N T

EMI	CE/FCC Class A
Safety operating	LVD, external adaptor UL c/us, CE, TUV, others
Temperature	0 – 40° C
OPOS	OPOS drivers for MSR, customer display, cash drawer
Dimensions (WxDxH)	folded - 361 x 254 x 81mm At 55° viewing angle - 361 x 232 x 255mm
Weight	3.7kg
Compatible O/S	Windows 7 Pro, POSready 7, POSready 2009, Linux
Standard colour	grey

O P T I O N S

MSR	3 track ISO, OPOS support
Dallas key reader	mounts to any of 4 mounting points
Fingerprint reader	mounts to any of 4 mounting points
Customer display	20 characters x 2 lines VFD (rear display)
2 nd screen	10.1" - 16:9 format - 1024 x 600 TFT LED
WI FI	802.11 b/g/n, internal
SSD	
Resistive touch panel	
Optional colours	available upon request - please contact us

